



SKU: 0110-0244

Category: Cards/Units

# High Density Remote POTS (HD R-POTS)

The High Density Remote Plain Old Telephone Service (HD R-POTS) plug-in card is a 24-port, loop start subscriber termination card. With support for 24 subscribers per card, the HD R-POTS card dramatically increases the capability of the Tellabs 1000 HD CBA to support high-density applications.

## Features

- TR-008 and GR-303 only
- Call Message Waiting Indicator (CMWI)
- Remote test access to metallic tip and ring
- 1830W loop length resistance (including station)
- 900 Ohm structural impedance
- Forward disconnect
- On-hook transmission (CLASS) capability
- Twenty-four (24) 2-wire circuits

## Highlights

### Ease of Operations

The HD R-POTS card has two LED indicators on the front panel. A green BUSY LED indicator, when lit, indicates that the HD R-POTS circuit is busy or is being tested and must not be removed from service. A flashing red FAIL LED indicates that there is illegal signalling on any one circuit. A red FAIL LED indicates that the unit has failed.

### Mechanized Loop Testing

The HD R-POTS also supports multiple loop testing systems including Mechanized Loop Testing (MLT).

### High Density Analog Voice

The HD R-POTS supports a loop length resistance of 1830 Ohms, ring cadence following, local ring trip, on-hook transmission between ring-bursts, and forward disconnect. The card supports Call Message Waiting Indicator (CMWI).

## Specifications

### LEDs

- Solid Red: Plug-in card failure
- Flashing Red: Illegal signalling on at least one circuit
- Green: At least one circuit is busy or being tested

### Test and Measurement

- Remote test access to metallic tip and ring

### Signaling

- On-hook detection threshold: > 9.0 kOhms
- Off-hook detection threshold:
- Open ckt. voltage - on hook transmission mode: 42.5 V minimum
- Open ckt. voltage - normal mode (battery -52 V): 44-46 Vdc minimum
- Loop current (constant): 25 mA, 20 mA minimum @ 1830 Ohms
- Maximum loop length including station: 1830 Ohms (for DC supervision)
- Ring trip delay (85 Vrms, 20 Hz):
- Ring trip detector (85 Vrms, 20 Hz): > 2000 Ohms
- Pulse distortion (pw > 25 ms):

- End to end signaling delay:

## Audio

- Longitudinal balance:  $x > 58$  dB (200 Hz - 1.0 kHz) and  $x > 53$  dB @ 3.0 kHz
- Two wire return loss: ERL  $> 28$  dB and SRL  $> 20$  dB
- Maximum VF overload level: +5.0 dBm
- Total loss (DLC loss + cable loss @ 8 dB, 1000 Hz, 70°F), #22 AWG cable = 17.391 kft., #24 AWG cable = 13.699 kft. and #26 AWG cable = 10.830 kft.
- Nominal loss (referenced to 2-wire 900 W): -2.0 dBm  $\pm$  0.5 dB
- Nominal input impedance: 900 Ohms  $\pm$  2.16  $\%$
- Companding:  $\mu$ -Law

## Environmental

- Humidity: 5% - 95%, non-condensing
- Storage temperature: -40°C to +70°C (-40°F to +158°F)
- Operating temperature: -40°C to +65°C (-40°F to +149°F)

## Physical

- Weight: 20 lbs (9.07 kg)
- Depth: 12.0 in (30.5 cm)
- Width: 19.0 in. (48.3 cm)
- Height: 12.25 in. (31.1 cm)

## Compliance

- TR-008
- GR-1089-CORE
- GR-303-CORE

## Software

- Minimum base software FP16 and higher

## Management

- Craft User Interface (CUI)
- Tellabs Panorama Element Management System (EMS)